

HIGEN		INDUCTION MOTOR DATA SHEET		40 HP - 2 P	
MODEL: KMI-40HU3		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		180L		OUTPUT 30 kW 40 HP	
ENCLOSURE		☐ DRIP PROOF		POLES 2 POLES	
		☒ TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		☐ Increased Safety Exp.-proof		☐ D.O.L ☒ Y-△ ☐ REACTOR (%TAP) ☐ V.V.V.F ☐ SOFT-STARTER	
PROTECTION		IP 44		STARTING METHOD	
METHODS OF COOLING		☐ SC ☒ FC ☐			
FREQUENCY		60 Hz		RATED VOLTAGE 380 V V V	
PHASE		3 PHASE		CURRENT	
SERVICE FACTOR		1.15		NO LOAD 15.5 A A A	
INSULATION CLASS		F CLASS		FULL LOAD 59.2 A A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				STARTING 455.9 A A A	
RES. METHOD		105 °C		EFFICIENCY	
THERMO. METHOD		°C		AT 1/2 LOAD %	
LOCATION		☒ INDOOR ☐ OUTDOOR		AT 3/4 LOAD %	
ALTITUDE		1000 m		AT FULL LOAD 89.0 %	
HUMIDITY		80 %		POWER FACTOR	
AMBIENT TEMPERATURE		-10~40 °C		AT 1/2 LOAD %	
RATING		☒ CONT. ☐ %ED		AT 3/4 LOAD %	
NEMA DESIGN		B		AT FULL LOAD 86.5 %	
MOUNTING		☒ B3 ☐ B5 ☐ V1 ☐ B3B5		SPEED (AT FULL LOAD) 3550 rpm	
BEARING		TYPE BALL		TORQUE	
		DEVN-DE 6312ZZC3 / 6309ZZ		FULL LOAD 8.2 kg-m 100%	
		LUBRICANT GREASE		LOCKED ROTOR 14.8 kg-m 180%	
COUPLING METHOD		☒ DIRECT ☐ V-BELT		BREAKDOWN 18.1 kg-m 220%	
SHAFT				NOISE LEVEL 91.0 dB(A)	
EXTENSION		SINGLE		VIBRATION 25.0 μm	
EXTERNAL THRUST				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
TERMINAL BOX				(AT DIRECT ON-LINE) 16.3 kg-m ²	
MAIN		☒ STEEL ☐ AL ☐ CAST		Motor GD ² 0.5309 kg-m ²	
AUX.		☐ YES ☒ NO		MOTOR APPROX. WEIGHT 224.0 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING MUNSSELL NO. 7.1 B 4.0/0.9	
APPLICATION STANDARDS		KS.IEC		THICKNESS ☒ STANDARD ☐ μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-H-180L-CA		
WINDING			S-T CURVE ST-KMI-40HU3		
TYPE			TERMINAL BOX DIMENSION TB-2M95115		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN STANDARD.					
FC : FAN COOLED SC : SELF COOLED			DATE PREPARED CHECKED APPROVED		
			2008-05.02 J.S.PARK J.S.PARK H.T.KIM		